

**SHRI TULJA BHAVANI COLLEGE OF ENGINEERING,
TULJAPUR 413 601 DIST. OSMANABAD**

Ph. No. 02471-242016. 243603

webs: stbceet.org.in

e-mail-stbceet@gmail.com

Ref. No. STBECT/STORE//2023/ 61\

Date: 18/02/2023

To,



Sub :- Quotation for Providing Fixing Factory made steel Door

Sir,

You are hereby requested to send your sealed quotation by Post / Speed post / Currier/by hand for the Providing Fixing Factory made steel Door as per the subjects to the following terms & conditions

- 1] The rates should be quoted with all taxes **including GST**.
- 2] Providing Fixing Factory made steel Door to be done by Authorized service provider. The required Forms and documentation for the same will be provided by college.
- 3] 100% payment will be made only after receipt of Providing Fixing Factory made steel Door in good condition by RTGS / NEFT / Cheque only & after satisfaction report of concerned authority.
- 4] 2% income tax will be deducted from the final bill as per IT rules.
- 5] The make and specifications of work should be mentioned clearly as per our requirement only in the quotation
- 6] Quotation should be in sealed cover subscribed as "Quotation for Providing Fixing Factory made steel Door".
- 7] Right to reject any or all quotation rest with the undersigned without giving any Reason.
- 8] Sealed quotations will be accepted in between Form Date: 21/02/2023 To Date: **27/02/2023 at 5.00pm**. Also Quotation displayed on our college website: www.stbect.org.in The quotation will be opened on 28/02/2023 Time 5:00PM

SR. NO.	Name of Items and Specification	Req. Qty/Nos	Rate per sqm	Total Approx. Amount inclusive of GST
1	Providing & fixing factory made steel door of single leaf external embossed wood finish type with A) frame size 100x58 mm conforming to IS : 4351-2003, 1.2 mm thick pre galvanized sheet with mitred and welded cones, frame stretches, hinge reinforcing plates, fixing plates, fixing plates and hardware mounting plates and polyurethane foam infill b) shutter of thickness 46 mm made of 0.8 mm thick slip coated pre galvanized steel sheet on both sides conforming to ASTM A527/ASTM A525, BS 2989 1994, IS 277 Zinc cating 120 GSM. Lock formed panels with internal stiffeners of 3mm thick made of galvanized sheet, 3 mm thick hinge reinforcing hardware mounting plates and lock protection with honey comb craft paper infill of thickness 150 GSM of load bearing capacity 500 kilogram/One square metre C) Finish Powder coated surface finished with thermosetting polyurethane paint of Aliphatic grade of thickness 60 micron d) Accessories min 8 Anchor fastener of HILTI to make, min 3ss Ball bearing butt hinges of dorset make, mortise lock SS Tower bolt of 200 mm size eye hole, door stopper complete	3.24 Sq.M		

**PRINCIPAL
PRINCIPAL**

S T B. College of Engg, Tuljapur